

**WEST**

Generate Collection

Print

L1: Entry 20 of 82

File: JPAB

Jun 15, 1988

PUB-NO: JP363142683A  
DOCUMENT-IDENTIFIER: JP 63142683 A  
TITLE: AVALANCHE PHOTODIODE

PUBN-DATE: June 15, 1988

## INVENTOR-INFORMATION:

NAME

COUNTRY

FUJIWARA, ICHIRO

MATSUDA, HIROSHI

ITO, KAZUHIRO

NAGATSUMA, KAZUYUKI

OUCHI, HIROBUMI

## ASSIGNEE-INFORMATION:

NAME

COUNTRY

HITACHI LTD

APPL-NO: JP61288801

APPL-DATE: December 5, 1986

US-CL-CURRENT: 257/438

INT-CL (IPC): H01L 31/10

## ABSTRACT:

PURPOSE: To form a low-noise, high-speed and high-sensitivity avalanche photodiode (APD) by a method wherein an InP and InGaAs doping superlattice of graded energy-band structure is used as an electric-field limiting layer.

CONSTITUTION: A buffer layer 2, a light-absorbing layer 3, an InP and InGaAs superlattice 5, an N- InP layer 6 are grown in succession on a substrate 1. Then, after Cd has been diffused at a low temperature and a guard ring 7 has been formed, a main uncton 8 is formed by selective thermal diffusion of Zn. A passivating film 9 is a three-layer structure of PSG/SiO<sub>2</sub>/SiN; an antireflection film 10 is composed of SiN. Lastly, a P-type ohmic electrode 11 and an N-type ohmic electrode 12 are formed. A carrier generated in the light-absorbing layer 7 passes through an electric-field limiting layer, is avalanche-multiplied inside a carrier-multiplying layer and reaches a P-N junction. Because an InP and InGaAs superlattice is used as the carrier-multiplying layer, the ratio of an ionization factor for an electron and a hole becomes big and the S/N ratio is improved.

COPYRIGHT: (C)1988,JPO&amp;Japio

